

N1404-1008

Revision: A


INDUSTRY APPROVALS

National Electrical Code
UL Standard 13
National Electrical Code
UL Standard 1424

Article 725
Type CL3P
Article 760
Type FPLP

EU Directive 2011/65/EU

RoHS Compliant



CONSTRUCTION

Component	Description	Specification
Conductor:	14 AWG (19/.0117) Bare Copper	0.072" Nominal diameter
Insulation:	0.010" Wall, FRPVC	0.092" Nominal diameter
Cable Assembly:	4 Conductors with a 7.50" LHL	0.217" Nominal diameter
Ripcord:	Yes	
Jacket:	0.014" Wall, FRPVC	0.247" ± .012" diameter
Sequential Footage		Every 2 feet
Print Legend:	NORTHERN (R) 14 AWG – N1404-1008 -- (UL FILE NUMBER) (UL) CL3P OR FPLP --- ROHS -- MADE IN USA (DATE CODE) (SEQ FT) (PRINT EVERY 2 FT)	

ELECTRICAL AND PHYSICAL PROPERTIES

Temperature:	-0°C to +75°C
Voltage:	300 Vrms (Maximum)
Conductor Resistance (DCR):	2.62 Ohms/1000ft (Maximum) @ 20°C
Capacitance (Cond-Cond):	36.0 pF/ft (Nominal) @ 1kHz
Characteristic Impedance:	53.0 Ohms (Nominal) @ 1MHz

CONDUCTOR COLOR CODE

Conductor	Color
1	Black
2	Red
3	White
4	Green

JACKET COLOR AND PACKAGING

N1404 – 1008 – XX XX

Jacket color

Put-up


PUT-UP

11	1000 Foot Reel
51	500 Foot Reel

JACKET COLOR

01	White	05	Yellow	09	Gray(slate)
02	Black	06	Blue	10	Purple
03	Red	07	Brown	11	Beige
04	Green	08	Orange	15	Natural

MADE IN



U. S. A.

* Some Put-Ups and Colors Require Special Order

Note: Specification subject to change without notice