

Part Number: NFKY1GHZWH
 Base Color



NFKY1GHZWH

Dimensions:

Depth	30.00 mm 1.181 in
Height	16.50 mm 0.650 in
Width	16.50 mm 0.650 in

Construction Materials:

Housing	Brass W/ Nickel Plating
Seizing Pin	360° Beryllium Bronze W/ Gold Plating
Insulator	Nylon Dielectric Blue
Plastic Material	ABS 94V-0
Nut Material	Iron Plated W/ Nickel Over Copper

General Specifications:

F-Type Female to Female

Environmental Specifications:

Flammability Rating	UL 94 V-0
Safety Standard	cUL I UL
Relative Humidity	Up to 93%, Non-Condensing
Operating Temperature	-40°C to + 65°C (-40 °F to + 149 °F)


Mechanical Characteristics:

Seizing Pin (Accepts Center Conductors)	Range (0.64 mm - 1.07 mm Diameter)
Holding Force	>160 Grams (Initial)
	>120 Grams (After Insertion)
Housing Shall Support	2.2Kg Force (Min) Applied to Insulator
	From Either Direction


Electrical Characteristics:

Frequency Range	DC -1HGz
Insertion Loss	< 0.2 dB
Return Loss	> 30dB
Contact Resistance	< 4 Milliohms

Dimensions:



SIDE



FRONT

Note: Specification subject to change without notice