

4-in-1 HD ANALOG

4-in-1, Full HD 1080p Outdoor Eyeball Camera D-WDR, 2.8mm IR Lens, 60' IR Range





FEATURES:

- ◆ Multi Format (TVI, CVI, AHD, 960H)
- ◆ True Day/Night Mechanical IR Cut Filter
- ◆ 2.8mm Fixed Focal IR Lens
- ◆ 18 IR LED's / 60' IR Range
- ◆ UTC & Joystick Controllable OSD
- ◆ 3D Digital Noise Reduction
- ◆ 12 Volt DC Power
- ◆ IP66 Weatherproof



HDEIR60

CAMERA OVERVIEW:



INCLUDED ACCESSORIES:

Camera, User Manual, Mounting Screws,

SPECIFICATION	HDEIR60
Image Sensor	1/2.8" CMOS Sensor
Total Pixels	1984 x 1225
Active Pixels	1920 x 1080
Resolution	1920 x 1080 (1080p)
Scanning System	Progressive Scan
OSD (On Screen Display)	Dual OSD Access: Cable OSD Controlled / UTC Controlled (coaxial control)
D-WDR (Digital Wide Dynamic Range)	Open/Close
DNR (Digital Noise Reduction)	3D DNR - Auto, Manual (0~10)
Video Output	TVI, CVI, AHD & 960H (Selectable via OSD Cable)
Lens Type / Viewing Angle	2.8mm IR Lens - H: 105° V: 56°
IR Cut Filter	Built in Mechanical
Minimum Illumination	Color 0.01 Lux, B/W 0.0 Lux, IR LED ON
IR LED Count / Range	18 IR LED's / 60' Range / 850nm
S/N Ratio	More than 48dB
Sync System	Internal
Gamma Characteristics	y = 0.45 typ
White Balance	Gray/Pro/ MWB - R & B Gain 0~127 Adjustable
Back Light Compensation	Global / BLC 0-7 Adjustable
Day/Night	EXT / Auto / Color / B/W
Languages	English, French, Spanish, German, Italian (see OSD Menu for more)
Brightness	0 ~100 Adjustable
Power Input	12VDC Only
Power Requirement	100mA / 280 mA IR LED ON
Overall Camera Dimensions	3.7" x 3.3" (φ94 x 84mm)
Housing / Color	Aluminum / White
Weight	0.7lb / 318g
Operating Temperature	-14°F ~ 131°F
Weatherproof Rating	IP66

Note: Specification subject to change without notice