

3.5" IP, TVI, Analog Camera Service Monitor w/ ONVIF, PTZ Control & Cable Tester

IP35TM With
Hand Strap



IP35TM
Case



IP35TM With
Built-in Stand

SPECIFICATION

IP35TM

| | |
|----------------------------|--|
| Signal System | NTSC / PAL Auto Sensing |
| Display / Resolution | 3.5" Capacitive Touch Screen / 480 x 320 |
| Camera Capability | IP, HD-TVI & 960H Analog |
| Battery / Run Time | Internal Lithium Ion Polymer Battery / 8 Hour Continuous |
| Battery Charge Time | 3-4 Hours for Full Charge |
| Charger Type | 5VDC Wall Plug or USB to Mini USB Cable (included) |
| Supported IP Camera | Over 70 supported ONVIF, ACTI, Dahua, HIKVISION, Samsung, Honeywell, etc. (see manual for full list) |
| Supported IP Camera Format | H.264 / MPEG-4 / M-JPEG |
| Network Test | IP Address Scan, Link Test, Ping Test, Port Finder |
| LCD Adjustment | Brightness, Contrast, Saturation, Gray Scale |
| IPC Viewer | iVMS-4500, Easy Mobile, MEye, etc. |
| Network Port | 10/100M Lan Port - Auto Adapt, RJ45 |
| Port Flashing | Yes |
| Browser | History, Bookmarks, Saved pages |
| Wi-Fi | Speed 150M, for Wireless Camera Image / Browser |
| POE Power Output | Pass through POE Power Only - Using PSE-In Port |
| Auxiliary Power Output | 12VDC - 1Amp for Camera Power |
| Video Input / Video Output | 1Ch BNC In/Out (standard analog), 1ch TVI In (TVI Only) / 1.0 Vp-p |
| Audio Input/output | 1 x 3.5mm Stereo Jack/ No-Audio Output - Speaker only |
| Communication | RS485 for PTZ Control |
| Baud Rate | 600, 1200, 2400, 4800, 9600, 19200, 115200bps |
| Protocols | Pelco P & D, Samsung, Panasonic, Fastrax, SONY-EVI, LG-MULTIX, BOSCH OSRD, Hikvision, Kalatel, AD 168(M-B), etc. |
| UTC Control | Yes |
| UTP Cable Tester | Displays Connection Status, Cable Type & Wire Sequence |
| SD Card | 4G Micro SD Card Included, Support up to 32GB Max |
| Recording | Supports Snapshot (JPG) & Record Video to SD Card |
| Media Player | Supports 1080p Video & MKV Media Files |
| Sleep Mode | Yes - Quick Press Power Button to Sleep/Wake |
| Calculator | Built-in Calculator |
| LED Lamp | Built-in White Light LED |
| Dimensions / Weight | 194 x 112 x 48mm (HxWxD) / 540g (Tester Only) |

Note: Specification subject to change without notice

FEATURES

- ◆ 3.5" Capacitive Touch Screen Display (480x320 Res.)
- ◆ Compatible with IP, HD-TVI & 960H Analog Cameras
- ◆ Touch Screen OSD & Key Controllable
- ◆ Supports ONVIF IP Camera Testing
- ◆ Pass-Through POE for Powering IP Cameras
- ◆ Built-in Wi-Fi for IP Camera Testing / Browser
- ◆ POE Voltage Measurement & Cable Status
- ◆ Supports 1080p HD Video & MKV Media Files
- ◆ More than 70 Customized IP Camera Protocols
- ◆ PING Test, IP Address Scan & Port Finder
- ◆ BNC Input for HD-TVI Camera Testing
- ◆ UTC Compatible with HD-TVI Cameras
- ◆ BNC In/Output for Standard Analog/PTZ Testing
- ◆ Analog Color Bar Generator for Image Testing
- ◆ Supports RS485 for PTZ Control
- ◆ Video Recording & Snapshot to SD Card
- ◆ Included 4GB Micro-SD, Supports up to 32GB
- ◆ Built-in 3.5mm Audio Input Jack
- ◆ 8-Hour Lithium Ion Polymer Battery
- ◆ 12 Volt DC, 1-Amp Output for Powering Cameras
- ◆ LED Lamp, Calculator, Notepad & Other App Tools

INCLUDED ACCESSORIES

1. Deluxe Carry Case w/ Lanyard
1. Safety Lanyard for Tester
1. 5VDC Wall Charger
1. USB to Micro USB Charger Cable
1. BNC Patch Cable
1. 12VDC Cable for Camera Power
1. RS485 Cable w/ Alligator Clip
1. PC Audio Cable w/ Alligator Clip
1. CAT5/6 Cable Termination Block
1. User Manual