

## Pre-Made BNC & HDMI Cables

### RG59U Video Coax Cables, HDMI 2.0 Cables



CBL3BNC



CBL6BNC

CABLE TYPE	CBL3BNC	CBL6BNC
APPLICATION	VIDEO	VIDEO
JACKET	PVC	
CONNECTORS	BNC TO BNC	
LENGTH	3'	6'



HDMI3UL



HDMI6UL



HDMI15UL

SPECIFICATION	HDMI3UL	HDMI6UL	HDMI15UL
<b>Electrical Characteristics</b>			
Signal Bandwith		10Gbps	
Nominal Impedence with Tolerance		100Ω	
Nominal Compacitance		less 0.5pf	
Dielectric Strength		AC- 750V/1sec MIN	
Insulation Resistance		10MΩ	
Nominal Attenuation		300KHz	
<b>Physical Characteristics</b>			
Cable Bend Radius		75mm	
Package Type		Poly Bag	
<b>Conductor 1</b>			
Conductor Type		30AWG (1/0.254BC)	
Insulation		Foamed PE [0.65mm (White/Blue)]	
Drain Wire		30AWG (1/0.254BC)	
Shield		Aluminum Foil	
Braiding		16/4/0.12AL	
<b>Conductor 2</b>			
Conductor Type		30AWG (1/0.254BC)	
Insulation		HDPE 0.6mm	
<b>General</b>			
HDMI Cable Length	3'	6'	15'
Connector Type	19 Pin HDMI-A		
Plating	Gold		
Connector	PE (Inner Mould) / 45P PVC (Outer Mould)		
Jacket	Black PVC 6.0mm		
Approvals	ROHS/CE/UL		