



4-in-1 SERIES CAMERA MODELS	HDDWMIR HDDWMIRW	HDDWMVFIR HDDWMVFIRW	HDBIR60	HDBVFIR120	HDBWIDE	HDDWIDE	HDMC	HDMCCP	HDPIR
Image Sensor	2 Megapixel CMOS Image Sensor								
Max Resolution	1920 x 1080								
Multiple Formats	TVI - CVI - AHD - 960H Selectable via OSD Joystick								
Lens Size	3.6mm	2.8 ~ 12mm	3.6mm	2.8 ~ 12mm	2.5mm - 150° FOV	2.5mm - 150° FOV	3.6mm Standard	3.7mm Pinhole	3.7mm Pinhole
True D/N & IR Corrective	Yes	Yes	Yes	Yes	Yes	Yes	IR Corrective Only	IR Corrective Only	IR Corrective Only
Focal Type	Fixed	Varifocal	Fixed	Varifocal	Fixed	Fixed	Fixed	Fixed	Fixed
IR LED Count / Range	12 IR LED's - 60'	18 IR LED's - 90'	18 IR LED's - 60'	30 IR LED's - 120'	NA	24 IR LED's - 60'	NA	NA	NA
Wide Dynamic Range	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR	Digital WDR
Main Video Outputs	Single Main Output - Multiple Format Selectable via OSD Joystick								
UTC Control	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
OSD Joystick	Cable Mounted	Cable Mounted	Cable Mounted	Cable Mounted	Cable Mounted	Cable Mounted	Cable Mounted	Cable Mounted	Cable Mounted
Power Requirement	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC
Housing Color	Gray / White	Gray / White	White	White	Black	White	Black	Black	White
Temp / Weather Rating	-14°F ~ 122°F / IP66	-14°F ~ 122°F / IP66	-14°F ~ 122°F / IP66	-14°F ~ 122°F / IP66	-14°F ~ 122°F / IP66	-14°F ~ 122°F / IP66	14°F ~ 122°F / Indoor Only	14°F ~ 122°F / Indoor Only	14°F ~ 122°F / Indoor Only